

# XATS 400 JD T3

Purpose built for the most demanding job sites and conditions, Atlas Copco XATS 400 HardHat™ will stand the test of time.



*Atlas Copco*

## ALL THE OPTIONS NEEDED FOR YOUR SPECIFIC APPLICATIONS

The HardHat™ features a revolutionary polyethylene canopy design - the toughest in the industry. It will not rust, dent, corrode or fade, and it resists extreme temperatures. The canopy protects the compressor from damage at the work site, which helps reduce the cost of ownership and boost resale value. Because it will “take a beating” in a variety of applications, it's a ideal for the rental industry.

### Technical data

MODEL		XATS 400 JD T3
Actual Free Air Delivery*	CFM	400
Working Pressure @ Rated Flow	psi	150
Working Pressure Range	psi	58-175
Discharge Outlet Quantity		1 x 1 1/2" 2 x 3/4"
Oil Capacity	Gal (L)	6.3 (23.8)

Engine - John Deere		
Model		4045
Displacement	L	4.5
Cylinder		4
Emissions Level		Environment Canada Tier 3
Power	HP	125
Rated Speed (high)	RPM	2400
Rated Speed (low)	RPM	1500
Fuel Tank Capacity	Gal (L)	58 (219)
Fuel Consumption @ 100% FAD	Gal/hr (L/hr)	6.7 (25.5)
Sound Pressure Level @75% Load	dB (A)	76

Dimensions		
Trailer	in	161 x 71.5 x 70
Weight (wet), Trailer Mounted	lbs	4,470
Trailer (Skid Mounted)	in	113 x 71.5 x 65
Weight (wet), Skid Mounted	lbs	4,590

Photos and illustrations contained herein might depict products with optional and/or extra components which are not included with the standard version of the product and, therefore, are not included in a purchase of such product unless the customer specifically purchases such optional/extra components. We reserve the right to change the specifications and design of products described in this literature without notice. Not all products are available in all markets.

\*According to ISO1217 ed 3.2009 annex D

## STANDARD FEATURES

- HardHat™ Enclosure
- Extremely Reliable John Deere power with 5 year engine warranty
- Operates under widely varying climatic conditions, water-cooled engine, large capacity oil cooling system, high efficiency heavy-duty two-stage intake filters (with cartridge replacement indicators)
- Highly efficient oil extraction system means low oil consumption
- Large capacity fuel tank placed low for good road handling and easy filling
- Gull wing doors for easy access to engine and components
- Few moving parts, minimum mechanical wear
- Rugged and reliable, needing little maintenance
- Optional after-cooler / water separator & filtration system for cool, dry & clean air
- 400 CFM @ operating pressures from 58-150 PSI easily adjustable to meet the specified requirements of the job.
- Canada cold weather package, including synthetic oils, Thermostatic by-pass, Heavy duty battery and block heater

## OPTIONS

- Hose Reels (Single or Double)
- LoJack® Stolen Vehicle Recovery System
- Support Mounted Frame (less running gear)
- 2" Ball Hitch
- After-cooler w/ Water Separator
- P.F.F. After-cooler w/ Filtration & Water Separator
- Electric or hydraulic brakes
- Inlet Shutdown Valve

