

2935 90300 01 - June 2015 - Subject to Modifications without prior notice. Copyright 2015, Atlas Copco.

Technical data

| MODEL | | XATS 750 JD7 iT4 |
|-------------------------------|---------|-------------------------------|
| Actual Free Air Delivery | cfm | 750 |
| Working Pressure @ Rated Flow | psi | 150 |
| Working Pressure Range | psi | 100-175 |
| Discharge Outlet Quantity | | 1 x 1 ^{1/2} 2 x 3/4" |
| Oil Capacity | Gal (L) | ? |
| | | |

| Engine - John Deere | | |
|--------------------------------|---------------|-------------|
| Model | John Deere | 6068 |
| Displacement | L | 6.8 |
| Cylinder | | 6 |
| Tier | US EPA | iT4 |
| Power | НР | 250 |
| Rated Speed (high) | RPM | 2000 |
| Rated Speed (low) | RPM | 1300 |
| Fuel Tank Capacity | Gal (L) | 78 (295) |
| Fuel Consumption @ 100% FAD | Gal/hr (L/hr) | 11.5 (43.5) |
| Sound Pressure Level @75% Load | dB (A) | 76 |

| Dimensions | | |
|-------------------------------|-----|-----------------|
| Trailer | in | 190 x 79 x 84 |
| Weight (wet), Trailer Mounted | lbs | 7,800 (3,538) |
| Trailer (Skid Mounted) | in | 132 x 66.5 x 69 |
| Weight (wet), Skid Mounted | lbs | 6,700 (3,040) |

Photos and illustrations contained herein might depict products with optional and/or extra components which are not included with the standard version of the product and, therefore, are not included in a purchase of such product unless the customer specifically purchases such optional/extra components. We reserve the right to change the specifications and design of products described in this literature without notice. Not all products are available in all markets.

*According to ISO1217 ed 3.2009 annex D

STANDARD FEATURES

- Extremely Reliable John Deere power with 5 year engine warranty
- Interim Tier 4 exhaust emission compliance
- Operates under widely varying climatic conditions, water-cooled engine, large capacity oil cooling system, high efficiency heavy-duty two-stage intake filters (with cartridge replacement indicators)
- Highly efficient oil extraction system means low oil consumption
- Gull wing doors for easy access to engine and components
- Few moving parts, minimum mechanical wear
- Rugged and reliable, needing little maintenance
- Optional after-cooler / water separator & filtration system for cool, dry & clean air
- 750 CFM @ operating pressures from 58-150 PSI easily adjustable to meet the specified requirements of the job.

OPTIONS

- Cold Weather Package
- LoJack® Stolen Vehicle Recovery System
- Support Mounted Frame (less running gear)
- After-cooler w/Filtration & Water Separator
- Electric brakes





